



# Digital Input Modules

## 8-channel 24 VDC digital input modules



### M-1800: 8 digital inputs, sink type, 24 VDC

**Digital Inputs:** 8 channels  
**Type:** sink  
**On-state Voltage:** 24 VDC nominal, 11 to 28.8 VDC  
**Off-state Voltage:** 0 to 5 VDC  
**On-state Current:** 6 mA/point @ 28.8 VDC (max.)  
**Input Impedance:** 5.1K ohms (typical)  
**Filtering Time:** 1.5 ms (typical)  
**Common Type:** External common (single common)  
**Power Consumption:** 35 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O cable max. AWG14  
**MTBF:** 15,759,240 hrs (Database: Telcordia/Bellcore)



### M-1801: 8 digital inputs, source type, 24 VDC

**Digital Inputs:** 8 channels  
**Type:** source  
**On-state Voltage:** 24 VDC nominal, 11 to 28.8 VDC  
**Off-state Voltage:** 0 to 5 VDC  
**On-state Current:** 6 mA/point @ 28.8 VDC (max.)  
**Input Impedance:** 5.1K ohms (typical)  
**Filtering Time:** 1.5 ms (typical)  
**Common Type:** External common (single common)  
**Power Consumption:** 35 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O cable max. AWG14  
**MTBF:** 15,811,800 hrs (Database: Telcordia/Bellcore)



## 16-channel 24 VDC digital input modules



### M-1600: 16 digital inputs, sink type, 24 VDC

**Digital Inputs:** 16 channels  
**Type:** sink  
**On-state Voltage:** 24 VDC nominal, 11 to 28.8 VDC  
**Off-state Voltage:** 0 to 5 VDC  
**On-state Current:** 6 mA/point @ 28.8 VDC (max.)  
**Input Impedance:** 5.1K ohms (typical)  
**Filtering Time:** 1.5 ms (typical)  
**Common Type:** 16 channels for 2 COMs (single common)  
**Power Consumption:** 40 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O flat cable 20-pin  
**MTBF:** 11,659,560 hrs (Database: Telcordia/Bellcore)





**M-1601: 16 digital inputs, source type, 24 VDC**

**Digital Inputs:** 16 channels  
**Type:** source  
**On-state Voltage:** 24 VDC nominal, 11 to 28.8 VDC  
**Off-state Voltage:** 0 to 5 VDC  
**On-state Current:** 6 mA/point @ 28.8 VDC (max.)  
**Input Impedance:** 5.1K ohms (typical)  
**Filtering Time:** 1.5 ms (typical)  
**Common Type:** 16 channels for 2 COMs (single common)  
**Power Consumption:** 40 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O flat cable 20-pin  
**MTBF:** 11,694,600 hrs (Database: Telcordia/Bellcore)



**4-channel AC digital input modules**



**M-1450: 4 digital inputs, 110 VAC**

**Digital Inputs:** 4 channels, 110 VAC  
**On-state Voltage:** 120 VAC nominal, 85 to 132 VAC  
**Off-state Voltage:** 0 to 45 VAC  
**On-state Current:** 8 mA/point @ 132 VAC (max.)  
**Input Impedance:** 11K ohms (typical)  
**Common Type:** 4 channels for 2 COMs (single common)  
**Power Consumption:** 35 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O cable max. AWG14  
**MTBF:** 19,482,240 hrs (Database: Telcordia/Bellcore)



**M-1451: 4 digital inputs, 220 VAC**

**Digital Inputs:** 4 channels, 220 VAC  
**On-state Voltage:** 240 VAC nominal, 170 to 264 VAC  
**Off-state Voltage:** 0 to 45 VAC  
**On-state Current:** 12 mA/point @ 264 VAC (max.)  
**Input Impedance:** 22K ohms (typical)  
**Common Type:** 4 channels for 2 COMs (single common)  
**Power Consumption:** 35 mA @ 5 VDC  
**Isolation:** I/O to logic (photocoupler isolation)  
**Wiring:** I/O cable max. AWG14  
**MTBF:** 19,727,520 hrs (Database: Telcordia/Bellcore)



**: Ordering Information**

**Available Models**

- M-1800:** Modular remote I/O module with 8 DIs, sink type, 24 VDC, RTB, -10 to 60°C operating temperature
- M-1801:** Modular remote I/O module with 8 DIs, source type, 24 VDC, RTB, -10 to 60°C operating temperature
- M-1600:** Modular remote I/O module with 16 DIs, sink type, 24 VDC, 20-pin, -10 to 60°C operating temperature
- M-1601:** Modular remote I/O module with 16 DIs, source type, 24 VDC, 20-pin, -10 to 60°C operating temperature
- M-1450:** Modular remote I/O module with 4 DIs, 110 VAC, RTB, -10 to 60°C operating temperature
- M-1451:** Modular remote I/O module with 4 DIs, 220 VAC, RTB, -10 to 60°C operating temperature

## По вопросам продаж и поддержки обращайтесь:

Архангельск +7 (8182) 45-71-35  
Астрахань +7 (8512) 99-46-80  
Барнаул +7 (3852) 37-96-76  
Белгород +7 (4722) 20-58-80  
Брянск +7 (4832) 32-17-25  
Владивосток +7 (4232) 49-26-85  
Волгоград +7 (8442) 45-94-42  
Екатеринбург +7 (343) 302-14-75  
Ижевск +7 (3412) 20-90-75  
Казань +7 (843) 207-19-05  
Калуга +7 (4842) 33-35-03

Кемерово +7 (3842) 21-56-70  
Киров +7 (8332) 20-58-70  
Краснодар +7 (861) 238-86-59  
Красноярск +7 (391) 989-82-67  
Курск +7 (4712) 23-80-45  
Липецк +7 (4742) 20-01-75  
Магнитогорск +7 (3519) 51-02-81  
Москва +7 (499) 404-24-72  
Мурманск +7 (8152) 65-52-70  
Наб.Челны +7 (8552) 91-01-32  
Ниж.Новгород +7 (831) 200-34-65

Новосибирск +7 (383) 235-95-48  
Омск +7 (381) 299-16-70  
Орел +7 (4862) 22-23-86  
Оренбург +7 (3532) 48-64-35  
Пенза +7 (8412) 23-52-98  
Пермь +7 (342) 233-81-65  
Ростов-на-Дону +7 (863) 309-14-65  
Рязань +7 (4912) 77-61-95  
Самара +7 (846) 219-28-25  
Санкт-Петербург +7 (812) 660-57-09  
Саратов +7 (845) 239-86-35

Сочи +7 (862) 279-22-65  
Ставрополь +7 (8652) 57-76-63  
Сургут +7 (3462) 77-96-35  
Тверь +7 (4822) 39-50-56  
Томск +7 (3822) 48-95-05  
Тула +7 (4872) 44-05-30  
Тюмень +7 (3452) 56-94-75  
Ульяновск +7 (8422) 42-51-95  
Уфа +7 (347) 258-82-65  
Хабаровск +7 (421) 292-95-69  
Челябинск +7 (351) 277-89-65  
Ярославль +7 (4852) 67-02-35

**сайт: [moxa.pro-solution.ru](http://moxa.pro-solution.ru) | эл. почта: [mhk@pro-solution.ru](mailto:mhk@pro-solution.ru)  
телефон: 8 800 511 88 70**